

## Fiche - 93120105 - Tunsggram




**Ampoule LED tube stik - Tunsggram -  
E27 - 14W - 4000K - 1600LM**


Réf 93120105

**4.20€<sup>TTC\*</sup>**

Voir le produit : <https://www.domomat.com/65954-ampoule-led-tube-stik-tunsggram-e27-14w-4000k-1600lm-tunsggram-93120105.html>

*Le produit Ampoule LED tube stik - Tunsggram - E27 - 14W - 4000K - 1600LM  
est en vente chez Domomat !*





## LED Stik G5

LED14/STIK/840/220-240V/E27/BX  
93120105

### Product information

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years\*. That's a long time you can spend not worrying about light bulbs.

#### Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years\*
- 3 colour options - 3000K, 4000K & 6500K
- Always ready - instant brightness
- No mercury - worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours

according to Tungsram Standard Warranty conditions

- Based on 2.7 hours of per day use.

---

## Application areas



Retail



Hospitality



Home

## Product data

Product Code	93120105
Product description	LED14/STIK/840/220-240V/E27/BX
Direct Shipment pair	93120129 - LED14/STIK/840/220-240V/E27/BX DS
Nominal Length [mm]	109
Net weight per piece [g]	39
Dimmability	No
Brand	Tungsräm
Cap/Base	E27

## Performance data

Color consistency (SDCM)	6
Rated efficacy [lm/W]	115.23
Energy efficiency class (EEC)	E
Rated life L70/B50 [h]	15000
Input Frequency [Hz]	50/60
Nominal correlated colour temperature (CCT) [K]	4000
Nominal lumens [lm]	1600
Colour Rendering Index (CRI) [Ra]	80

## Electrical data

Nominal lamp power factor...	0.7
Operating Temperature (MIN) [°C]	-10
Operating Temperature (MAX) [°C]	40
Starting time (sec)	0.5
Number of switching cycles	50000
Nominal lamp voltage range [V]	220-240
Nominal power [W]	14

## Logistic data

Shipment	Standard
DUN Code	15994100085529
EAN Code	5994100085522
Pack Quantity	1/12
Product status	Available

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Link to EPREL \(HTTP\)](#)

[Datasheet \(PDF\)](#)

[Images \(HTTP\)](#)

[Declaration of Conformity \(PDF\)](#)