



LED Stik G5

LED14/STIK/830/220-240V/E27/BX
93120101

Product information

LED Stik illuminates spaces with light instantly. Its sleek cylindrical shape fits in place of a traditional incandescent bulb and some sockets where a traditional bulb or CFL doesn't fit. Replace a 40W, 60W, 75W & 100W incandescent with an LED Bright Stik and keep saving for the next 15 years*. That's a long time you can spend not worrying about light bulbs.

Features & benefits

- LED technology for energy saving
- Redesigned shape with multiple advantages:
- To fit in more fixtures compared to CFL
- Optimised for omni-directional light distribution
- Space-saving benefits on-shelf
- 240 degree Beam angle
- Replaces a standard 40W, 60W, 75W & 100W bulb
- Rated life of 15 years*
- 3 colour options - 3000K, 4000K & 6500K
- Always ready - instant brightness
- No mercury - worry-free use and disposal
- Warranty: 2 years with maximum 8 000 burning hours

according to Tungsram Standard Warranty conditions

- Based on 2.7 hours of per day use.

Application areas



Retail



Hospitality



Home

Product data

Product Code	93120101
Product description	LED14/STIK/830/220-240V/E27/BX
Direct Shipment pair	93120125 - LED14/STIK/830/220-240V/E27/BX DS
Nominal Length [mm]	109
Net weight per piece [g]	39
Dimmability	No
Brand	Tungsräm
Cap/Base	E27

Performance data

Color consistency (SDCM)	6
Rated efficacy [lm/W]	115.23
Energy efficiency class (EEC)	E
Rated life L70/B50 [h]	15000
Input Frequency [Hz]	50/60
Nominal correlated colour temperature (CCT) [K]	3000
Nominal lumens [lm]	1521
Colour Rendering Index (CRI) [Ra]	80

Electrical data

Nominal lamp power factor...	0.7
Operating Temperature (MIN) [°C]	-10
Operating Temperature (MAX) [°C]	40
Starting time (sec)	0.5
Number of switching cycles	50000
Nominal lamp voltage range [V]	220-240
Nominal power [W]	14

Logistic data

Shipment	Standard
DUN Code	15994100085383
EAN Code	5994100085386
Pack Quantity	1/12
Product status	Available

Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Link to EPREL \(HTTP\)](#)

[Datasheet \(PDF\)](#)

[Images \(HTTP\)](#)

[Declaration of Conformity \(PDF\)](#)

