


D12780 | Springmasters




**Lot de 5 ressorts de compression
RS Pro - Acier - Coupé/ Rectifié -
1.63N/mm - 135x22mm**
Réf 121-286

10.76€^{TTC*}

Voir le produit : <https://www.domomat.com/56899-lot-de-5-ressorts-de-compression-rs-pro-acier-coupe-rectifie-163nmm-135x22mm-rs-pro-121-286.html>

*Le produit Lot de 5 ressorts de compression RS Pro - Acier - Coupé/ Rectifié -
1.63N/mm - 135x22mm
est en vente chez Domomat !*



Datasheet

RS Pro Steel Alloy Compression Spring, 135mm x 22mm, 1.63N/mm

RS Stock No: **121-286**



Product Details

RS Pro stainless steel alloy compression spring measures 135 x 22 mm and has a spring rate of 1.63 N/mm. It handles a load of 158.87 N at a minimum working length of 38.8 mm. This spring features right hand helix construction.

Features and Benefits

- Wire diameter ends up to 0.8 mm are squared and ungrounded
- Wire diameter ends 1 mm and over are squared and ground
- Manufactured with a right hand helix



ENGLISH

Specifications:

Ends	Closed (Square)/Ground
Material	Steel Alloy
Free Length	135 mm
Load at Minimum Working Length	158.87 N
Minimum Working Length	38.8 mm
Outside Diameter	22 mm
Spring Rate	1.63 N/mm
Wire Diameter	2 mm