D12320 | Springmasters

Lot de 5 ressorts de compression RS Pro - Acier - Coupé/ Rectifié - 0.72N/mm - 94x17.25mm

Réf 121-185

7.64€TTC*

Voir le produit :
https://www.domomat.com/56900-lot-de-5-ressorts-de-compression-rs-pro-acier-coupe-rectifie-072nmm-94x1725mm-rs-pro-121-185.html

Le produit Lot de 5 ressorts de compression RS Pro - Acier - Coupé/ Rectifié - 0.72N/mm - 94x17.25mm est en vente chez Domomat !



* : Prix sur le site Domomat.com au 12/10/2024. Le prix est susceptible d'être modifié.

ENGLISH

Datasheet

RS Pro Steel Alloy Compression Spring, 94mm x 17.25mm, 0.72N/mm

RS Stock No: **121-185**

Product Details

RS Pro stainless steel alloy compression spring measures 94 x 17.25 mm and has a spring rate of 0.72 N/mm. It handles a load of 54.23 N at a minimum working length of 18.5 mm. This spring features right hand helix construction.

Features and Benefits

- Wire diameter ends up to 0.8 mm are squared and ungrounded
- Wire diameter ends 1 mm and over are squared and ground
- Manufactured with a right hand helix

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.

ENGLISH

Specifications:

Ends	Closed (Square)/Ground
Material	Steel Alloy
Free Length	94 mm
Load at Minimum Working Length	54.23 N
Minimum Working Length	18.5 mm
Outside Diameter	17.25 mm
Spring Rate	0.72 N/mm
Wire Diameter	1.25 mm

RS, Professionally Approved Products, gives you professional quality parts across all products categories. Our range has been testified by engineers as giving comparable quality to that of the leading brands without paying a premium price.