

Spot Bali R Indigo



Spot encastré basse luminance Bali R Indigo - GU10 - 10W max - PAR16 - Noir mat
Réf DO51305 **16.51€^{TTC*}**

<https://www.domomat.com/64841-spot-encastre-basse-luminance-bali-r-indigo-gu10-10w-max-par16-noir-mat-indigo-do51305.html>



Spot encastré basse luminance Bali R Indigo - GU10 - 10W max - PAR16 - Noir/champagne
Réf DO51308 **18.43€^{TTC*}**

<https://www.domomat.com/65111-spot-encastre-basse-luminance-bali-r-indigo-gu10-10w-max-par16-noirchampagne-indigo-do51308.html>



Spot encastré basse luminance Bali R Indigo - GU10 - 10W max - PAR16 - Noir/Argent
Réf DO51317 **18.43€^{TTC*}**

<https://www.domomat.com/65112-spot-encastre-basse-luminance-bali-r-indigo-gu10-10w-max-par16-noirargent-indigo-do51317.html>



Spot encastré basse luminance Bali R Indigo - GU10 - 10W max - PAR16 - Blanc/Champagne
Réf DO51349 **18.43€^{TTC*}**


<https://www.domomat.com/65113-spot-encastre-basse-luminance-bali-r-indigo-gu10-10w-max-par16-blancchampagne-indigo-do51349.html>



Spot encastré basse luminance Bali R Indigo - GU10 - 10W max - PAR16 - Blanc/Argent
Réf DO51353 **18.43€^{TTC*}**


<https://www.domomat.com/65114-spot-encastre-basse-luminance-bali-r-indigo-gu10-10w-max-par16-blancargent-indigo-do51353.html>

Retrouvez tous les produits de la catégorie
Spot encastrable intérieur Indigo
chez Domomat !



BALI R GU10

- Fixed round recessed spotlight.
- Low luminance reflector.
- Fastened with springs.



CODE	COLOR	MATERIAL	SOCKET	AC	Watt Max	LAMP
DO51305	MATT BLACK	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51308	MATT BLACK - CHAMPAGNE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51317	MATT BLACK - SILVER	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51330	MATT WHITE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51349	MATT WHITE - CHAMPAGNE	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED
DO51353	MATT WHITE - SILVER	ALUMINIUM	GU10	AC 230V	13W	PAR16 LED



MATT BLACK



MATT BLACK -
CHAMPAGNE



MATT BLACK - SILVER



MATT WHITE



MATT WHITE -
CHAMPAGNE



MATT WHITE - SILVER



Recessed ceiling mounting only.



Indoor use only.



Protected against the ingress of solid bodies greater 12 mm. No protection against the ingress of liquids.



Protection against an impact energy of 0,20 Joule.



Live parts are equipped with additional isolation protection, such as reinforced or double insulation.



Hole cut to insert luminaire (75mm)



Minimum ceiling height to insert luminaire. (140mm)



Product in conformity CE.




Test on 650°.



Product can not be covered after installation even with insulation.



3 years warranty.



Replaceable light source by an end-user.